

The Eigenfrequencies of a Real Structure Excited by an Internal Noise

B. Benabdelkader¹ --- M. Elmir² --- A. Touhami³

^{1,2}TAHRI Mohamed University of Bechar, Bechar, Algeria ³ University Center of Tindouf, Tindouf, Algeria

Abstract

This research work attempts to present an experimental study on the structure of the former laboratory of vibration and structural dynamics in the technological hall that belong to Bechar University. This study tries to determinate the real behavior of this structure. The structure is exited by background noise generated by a vibrating table compacting concrete, placed inside the laboratory, after we simulate this noise with an electrodynamics shaker. The response of the structure was captured by a tri-axial accelerometer. The experimental results are presented under an auto spectrum, for determining the eigenfrequencies of the structure, this values are compared with those obtund from a numerical simulation bases on the finite elements method.

Keywords: Vibration, Background noise, Dynamic, Excitation, Tri-axial accelerometer, Eigenfrequency.

1. Introduction

The background noise is a series of vibrations due to industrial machinery, human activities, wind, traffic ... etc... Frequencies of background noise belong to a domain that does not exceed 100 Hz and can set a limit average 1Hz as the "border" between natural and anthropogenic noise.

This solicitation requires no hardware means. If we compare with the various stresses, such as measurements in shock, there are several advantages, among which are:

- The experimental time is reduced
- The absence of excitation material,
- The cost of the measures is very low compared to other solicitations.

Background noise contains all frequencies likely to excite the structures, so a single measurement is sufficient to obtain a complete response. Accelerations produced are of the order of 10^{-5} g, while the exciter produces harmonic accelerations of the order of 10^{-3} g and shocks generate accelerations of the order of 10^{-2} g (g is the acceleration of gravity).Our aim is to study experimentally the influence of background noise of machines installed inside the laboratory on the behavior of the structure.

2. Experimental Part

The laboratory is a part of the large steel structure (Fig.1), with an area of (5x8) m² consisting of six (06) poles type HEA240 and five (05) beams type IPE270. We chose the middle pole of the wall which separates the laboratory from outside, to implement the media used tri-axial accelerometer (Fig.2).



Fig-1. The structure of technological hall



Fig-2. Interior view of the studied structure laboratory

To the study and analysis of the dynamic behavior of our structure, we used the equipment the firm Brüel & Kjær (Fig.3 and 4):

- A three-way accelerometer (tri-axial) type 4506;

- A multi-channel analyzer type 2825.



Fig-3. Tri-axial accelerometer type 4506



Fig-4. Multi-channel analyzer type 2825

Our experimental test is based on the excitation of the structure, using the vibrating table for compacting concrete specimens, placed inside the laboratory. The response of the structure is measured by a tri-axial accelerometer, and it is analyzed and processed in an acquisition channel, called multi-channel analyzer.

The values obtund from a numerical simulation has allowed us to have eigenfrequencies of the structure, and compare them with those deduced from the graphs resulting from the analyzer.

3. Results and Discussion

To deduce the eigenfrequencies of our structure, we will use a representation in the auto-spectrum form, witch is a representation of the amplitude as a displacement, velocity or acceleration as a function of frequency. This representation is marked by peaks that correspond to the natural frequencies of the structure studied.

Fig. 5, 6 and 7 are auto-spectrum of the response of the structure in the three directions x, y and z. The peaks of these curves represent the eigenfrequencies. The eigenfrequencies and eigenmode are shown in TAB I.

We limited our study the first six modes that correspond to the frequencies that belong to the domain of the background noise. From the results found, the motion of the structure is either flexure modes along the axis of x (mode 1 and 6) or torsional modes around the y axis (the other modes).





| Table-1. Eigenmodes, Eigenfrequencies and Damping Factor of | the Structure |
|---|---------------|
|---|---------------|

| Mode | 1 | 2 | 3 | 4 | 5 | 6 |
|----------------|------|------|------|------|------|------|
| Along x | 22 | 46 | 64 | 75 | 94 | 108 |
| Along y | | | | | | |
| Along z | | 46 | 68 | 76 | 94 | |
| Damping factor | 1.62 | 1.90 | 1.10 | 0.56 | 0.60 | 0.86 |

According to the results (TAB.1), the values of damping factors of the structure belong to a range of [0.6, 2] %. For low frequencies damping factors are in the order of 2%.

4. Numerical Simulation

To compare the experimental results and found it was a study by numerical simulation which is based on the finite element method.

The Fig. 8, 9 and 10 represent the first three eigenmodes found by numerical simulation.





The TAB II summarizes the values of the eigenfrequencies of the structure deduced experimentally and those of the numerical simulation.

| Table-2. Results Comparison | | | | | | | | | |
|-----------------------------|------|------|------|------|------|-----|--|--|--|
| Mode | 1 | 2 | 3 | 4 | 5 | 6 | | | |
| fexp | 22 | 46 | 64 | 74 | 94 | 109 | | | |
| fsim | 21.4 | 45.1 | 63.2 | 76.6 | 92.5 | 109 | | | |
| Relative error (%) | 2.8 | 2.0 | 1.3 | 1.9 | 1.6 | 0.9 | | | |

We note that these results are in good agreement which confirms the experimental results.

5. Conclusion

This excitation method has shown that the structure studied from steel structure, have not vertical movement when it is excited by a background noise of the machines or human activities inside this structure.

The numerical simulation showed and confirmed the experimental results. Eigenmodes expressed experimentally and numerically are very close with a relative uncertainty of about 3%.

References

- [1] A. Alvandi, *Contribution à l'utilisation pratique de l'évaluation dynamique pour la détection d'endommagements des ponts*, Thèse de doctorat. Ecole Nationale Française des Ponts et Chaussées, Oct 2003.
- [2] S. Bonnefoy-Claudet, *Nature du bruit de fond sismique : implications pour les études des effets de site,* Thèse de doctorat de l'Université Joseph Fourier de Grenoble, Dec 2004.
- [3] B. Benabdelkader, *Le bruit de fond dynamique appliqué à la détermination du comportement réel d'une structure*, Mémoire de Magister, Université de Bechar, Février 2008.
- [4] Benabdelkader, B., Elmir, M., Touhami A., *Le bruit de font du au trafic routier appliqué à la détermination du comportement réel d'une structure*, Séminaire International sur les Technologies Mécaniques, Tlemcen, Algérie, Décembre 2009.
- [5] Capozucca R., Cerri MN., Identification of damage in reinforced concrete beams subjected to corrosion, ACI Struct. J. USA, 97(6): 902–9, 2000.
- [6] Capozucca R., Cerri MN., Influence of reinforcement corrosion in the compressive zone–on the behaviour of RC beams, Eng. Struct., 25:1575–83, 2003.
- [7] Brüel & Kjær, Accelerometers and Conditioning document technique, Product catalogue(Denmark, February 2005).
- [8] Tiliouine, B., Dynamique des structures, Tome 1 : Aspects vibrations (GECOTEC Alger, 2000).
- [9] Castel A., François R., Arliguie G., Mechanical behaviour of corroded reinforced concrete beams, part. I: Experimental study of corroded beams, RILEM Materials and Structures 33: 539-544, 2000.
- [10] Castel A., François R., Arliguie G., Modèle de comportement mécanique du béton armé corrodé, C. R. Mécanique 330 : 45-50, 2002.
- [11] Quang Thanh Nguyen, Sabine Caré, Alain Millard, Yves Berthaud, Analyse de la fissuration du béton armé en corrosion accélérée. C. R. Mecanique 335: 99–104, 2007.
- [12] Cawley P., Adams RD., The location of defects in structures from measurements of natural frequencies, J. Strain Anal. Eng. Des., 14: 49–57, 1979.
- [13] Thyagarajan SK., Schulz MJ., Pai PF., Detecting structural damage using frequency response functions, Journal of Sound and Vibration, 210: 162–70, 1998.
- [14] Elmir M., Labbaci B. & Boutchicha D., Détection et identification de fissures dans les poutres par analyses modales numérique et expérimentale. 7^{ème} Séminaire International de Physique Energétique, 2-4.10.2004, Béchar, Algérie.

- Michele D., Antonino M., Vibrations of steel concrete composite beams with partially degraded connection and applications to damage detection, Journal of Sound and Vibration 320 101–124, 2009. Serridge, M. & Light T.R., Accéléromètres piézoélectriques de vibration, (Denmark, October 1988). [15]
- [16]